

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the  
Federal Communications Commission****By:****American TCB, Inc.  
6731 Whittier Avenue Suite C110  
McLean, VA 22101****Date of Grant: 12/23/2008****Application Dated: 12/22/2008****Nokia Corporation  
Joensuunkatu 7  
P.O. Box 86,  
Salo, 24100  
Finland****Attention: Tero Lehtinen , Product Certification Officer****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER: PYARM-413****Name of Grantee: Nokia Corporation****Equipment Class: PCS Licensed Transmitter held to ear****Notes: GSM/WCDMA cellular phone w/BT and WLAN**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BC	22H	824.2 - 848.8	0.537	0.1 PM	300KG7W
BC	22H	824.2 - 848.8	0.065	0.1 PM	300KG7W
BC	22H	826.4 - 846.6	0.056	0.1 PM	4M20F9W
BC	24E	1850.2 - 1909.8	1.023	0.1 PM	300KGXW
BC	24E	1850.2 - 1909.8	0.219	0.1 PM	300KG7W
BC	24E	1852.4 - 1907.6	0.162	0.1 PM	4M20F9W

Power Output is ERP for Part 22 and EIRP for Part 24. Body-worn operations are restricted to belt-clips, holsters or similar accessories that have no metallic component in the assembly and which provide at least 2.2 cm separation between the device and the users body. End users must be informed of the body worn requirements for satisfying RF Exposure compliance. The highest reported SAR values are: Part 22 Head: 1.11W/kg; Body-worn 0.93 W/kg; 850 WCDMA: Head 0.48W/kg; Body-worn: 0.38W/kg; PCS Band Head: 1.10 W/kg; Body-worn 0.25 W/kg; 1900 WCDMA: Head: 1.02; Body-worn: 0.24; Part 15 WLAN: Head: 0.21/kg; WLAN Body: 0.11W/kg. This device contains GSM/WCDMA functions that are not operational in U.S. Territories. This filing is only applicable for 850 MHz Cell and 1900 MHz PCS operations. This device contains a Bluetooth and WLAN transmitter. HAC rating M:3 2007

BC: The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.